

KRAUS MICON 252 BOARD SWITCH SETTINGS		
SW	SETTINGS	DESCRIPTION
1	OFF	VOLUME PULSE OUTPUT 10PPU (4mSEC WIDTH OR 26mSEC SEE SW 7)
	ON	VOLUME PULSE OUTPUT 100PPU (2mSEC WIDTH)
2	OFF	.030 UNITS SUPPRESSION AT RESET
	ON	.009 UNITS SUPPRESSION AT RESET
3	OFF	1000 INCOUNTS PER UNIT
	ON	378.4 INCOUNTS PER UNIT
4	OFF	INCOUNT = 1X INPUT FROM ENCODER
	ON	INCOUNT = 2X INPUT FROM ENCODER
5	OFF	DOLLARS CURRENCY MODE
	ON	ZERO DECIMAL PLACES IN PRICE PER UNIT AND \$ SALE.
6	OFF	NO IDLE FLOW SHUT DOWN
	ON	IDLE FLOW SHUT DOWN AT 1.5 MINUTES
7	OFF	NORMAL PULSE WIDTH ON PULSER OUTPUTS
	ON	LONG PULSE WIDTH ON PULSER OUTPUTS (ONLY VALID IF SW 1 IS OFF) (26mSEC)
8	OFF	NORMAL OPERATION
	ON	DISPLAY SELF TEST (DISPLAY CONTINUOUSLY CYCLES THROUGH "COLD START"
		SEQUENCE.